



PRESSURE

Smart Gauge Pressure Transmitter

Tek-Bar 3120B



Technology Solutions



1 FEATURES

- Digital communication HART protocol
- High accuracy up to $\pm 0.075\%$
- Various Output: 4-20 mA, digital signals
- Multiple temperature and linearity compensation to improve accuracy
- Fully-sealed and fully isolated silicon pressure sensor
- Superior stainless steel process flange
- Dual diaphragm overload protection, it can easily cope with overload tests
- 355° rotation display module

3 APPLICATIONS

- Food and Beverages
- Water and wastewater
- Oil and Gas
- Pulp and Paper
- Chemical

CONTACT US

📍 796 Tek Drive, Crystal Lake, IL 60014 USA

☎ +1 847 857 6076
+1 847 655 7428

✉ Email: tektrol@tek-trol.com

🌐 www.tek-trol.com

2 SPECIFICATION

Pressure type	Gauge Pressure
Reference accuracy	$\pm 0.075\%$ F.S., optional Enhanced Accuracy of $\pm 0.065\%$, $\pm 0.04\%$
Diaphragm materials	Hastelloy C
Measuring range	5.8 psig to 5800 psig
Stability	$\pm 0.2\%$ URL/5 year
Working humidity	5 to 100% RH at 104 °F
Output signal	4 to 20 mA with HART
Electrical connection	1/2" NPT Female conduit
Insulation resistance	≥ 20 M Ω at 100 VDC
Process connection	1/4" NPT Female
Working temperature	-40 °F to 180 °F (-40 °C to 82 °C)
Weight	About 3.43 lb (without mounting bracket and process connection accessory)
Testing standard	GB/T28474 / IEC60770
Media temperature	Silicon oil filling: -40 °F to 248 °F (-40 °C to 120 °C)
Protection class	IP66
Standard/flame proof	10.5-55 VDC
HART protocol	16.5-55 VDC, communication load resistance 250 Ω
Load resistance	0-2119 Ω for working condition, 250- 600 Ω for HART
Transmission distance	<3281 ft
Power consumption	≤ 500 mW at 24 VDC, 20.8 mA