



FLOW



Technology Solutions



Coriolis Mass Flowmeter

Tek-Cor 1100A

1 FEATURES

- Suitable for aggressive and contaminated media
- Measurement and display of percent water-cut for oil or water mixtures
- High rotation frequency and well-balanced measuring tubes
- Higher sampling and digital filtering
- High accuracy for measuring mass flow, density, temperature, and volume flow
- Can be used in extremely harsh conditions
- OLED with 2 line indication
- Measurement of net oil

3 APPLICATIONS

- Dairy plants
- Oil and Gas
- Process industry
- Chemical
- Food and Pharma

CONTACT US

796 Tek Drive, Crystal Lake, IL 60014 USA

+1 847 857 6076
+1 847 655 7428

Email: tektrol@tek-trol.com

www.tek-trol.com

2 SPECIFICATION

Repeatability	±0.05% (for 0.1% accuracy), ±0.1% (for 0.2% accuracy) or ±0.25% (for 0.5% accuracy)	
Accuracy	±0.1%, ±0.2% or ±0.5%	
Density Accuracy	0.001 g/cm ³	
Sensor options	U-series shaped/Micro-bend shaped/Triangle shaped	
Process media	Liquid, Gas	
Transmitter	Digital type/Analog type	
Power supply	18-28 VDC or 85-220 VAC	
Maximum pressure	3770 PSI (26 MPa)	
Output signal	4-20 mA and pulse, Optional: HART or Modbus RS485	
Process connections	DIN, ANSI flanges	
Electronics	Direct mount or Remote mount	
Diagnostic functions	Reset totalizer	
Graphic display	OLED	
Operating elements	3 optical keys for operator	
Additional features	Low flow cut-off, Oil and water content analysis, Zero calibration, Flow calibration, Long-term stability, Zero point adjustment, Conforms IEC 61362 (Industrial) EMC directive, Useful for all type of sensors i.e. U-shaped, Triangle shaped, Micro-bend shaped	
Temperature range	Direct mount	-58 °F to 257 °F (-50 °C to 125 °C)
	Remote mount	-58 °F to 392 °F (-50 °C to 200 °)
Process medium temperature	Up to -200 °C	